

▲Input Voltage 100-240VAC

▲Protections: short circuit/over load/over voltage/over temperature

▲IP20 Ingress protection

▲Power Factor 0.5

▲Efficiency $\geq 73\%$

▲Class II, SELV

▲5 years warranty



SPECIFICATION

Input	Rated input voltage	100-240VAC		
	Range of input voltage	90-264VAC		
	Frequency(Hz)	50/60 Hz		
	Power Factor	0.5±0.05@100-240VAC		
	Input Current max	0.1A MAX. @Full Load, 90VAC		
	Start-up time	<0.5S		
	Unload Power Consumption	≤0.3W		
	Inrush Current	10A MAX. @Full Load,240VAC		
	Leakage Current	<0.5mA(240VAC)		
Output	Constant Current	350mA	500mA	700mA
	Unload voltage	16VDC MAX.	12VDC	6VDC
	Voltage Range(VDC)	2.8-12VDC	2.5-8VDC	2.5-4VDC
	Rated load	4.2W Max.	4W Max.	2.8W Max.
	Current Accuracy	±5%		
	Voltage Regulation	≤3% @Full Load		
	Load Regulation	≤3%		
	Hold-up Time	1s max.@Full Load		
	Ripple& Noise Note.2	<35mAp-p	<50mAp-p	<70mAp-p
	Efficiency	≥73%@Full Load,230VAC		
Protection	Over Load Protection	105-120%		
		Protection type: Auto Resume		
	Over Voltage Protection	>16VDC	>12VDC	>6VDC
		Protection type: Auto Resume		
	Short circuit Protection	Protection type: Auto Resume		
Over Temperature protection	Protection type: Auto Resume			
Environment	Operating Temperature	-10℃...+50℃		
	tc	75℃		
	Storage Temperature	-20℃...+60℃		
	Humidity	10%-90%RH		
	Life time	>30,000h @50℃		
Others	Dimension	58.1X28.5X21(LXWXH)mm		
Safety & EMC	Safety standards	EN 61347-1; EN61347-2-13		
	EMC standards	EN55015; EN61000-3-2 Class A; EN61000-3-3		
	EMS	EN 61547;EN 61000-4-2 — Performance Criteria B; EN 61000-4-5 —500V; Performance Criteria C		
Note	1.All parameters NOT specially mentioned are measured at 240VAC input , rated load and 25℃ of ambient temperature. 2.Ripple & Noise are measured at 20MHz of bandwidth by using a 300mm twisted pair-wire terminated with a 0.1uF & 47 uF parallel capacitor.			

MECHANICAL SPECIFICATIONS

