



ZOUK is delicately designed and engineered for slim profile surface mounted and wall recessed light, featured low glare with screw-less appearance. Manufactured from LM6 Aluminium the housing is built to last and be situated in the the harshest of climates. The coating of Nano Ceramic film and double layer of durable paint ensures longevity. Built with the mindset of light comfort and soft visualization. Light source is CRI > 80 with an offering of 2700K, 3000K and 4000K. Available in various designs to compliment both commercial and residential applications.



Ordering code guide



Technical Data



Ordering Code :	7054-0-3-936-XX
Lamp :	LED
CCT :	3000 K
CRI :	CRI >80
SDCM :	SDCM = 3
Lamp Lumen :	1120 lm
Luminaire Lumen :	440 lm
Lamp Wattage :	8.5 W
Luminaire Wattage :	11 W
Efficacy :	40 lm/W
Ambient Temperature :	50°C
Lumen Maintenance	L70B10 >36,000 h
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	1.40 kg.



Icon definition

Specification

IEC Standard	IEC 60598-1 General Requirement						
	IEC 60598-2-1 Fixed Luminaires						
Protection	IP65 Class I						
IK Rating	Protection against mechanical impact IK07 on body and optical part.						
Luminaires Body Housing	High-pressure Die Cast Aluminium alloy body and components.						
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.						
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.						
Gasket	Weather resistant silicone gasket. Working temperature -40°C to +200°C.						
External Screws	External screws are in stainless steel with protection grease.						
Cable Entry	Cable entry protected by weather proof grommet. To be used with HO5RN-F/ HO7RN-F cable with 6~13mm. diameter.						
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.						
Driver	High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard.						
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.						
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.						
	Class1 luminaire provided with the earth connection.						
Caution	Installation work has to be carried on according to the enclosed installation manual.						
Color	<table><tr><td>Black O1</td></tr><tr><td>Graphite O2</td></tr><tr><td>Dark Grey O3</td></tr><tr><td>Aluminum Silver O4</td></tr><tr><td>White O6</td></tr><tr><td>Wooden Brown O7</td></tr></table>	Black O1	Graphite O2	Dark Grey O3	Aluminum Silver O4	White O6	Wooden Brown O7
Black O1							
Graphite O2							
Dark Grey O3							
Aluminum Silver O4							
White O6							
Wooden Brown O7							

Light Distribution

